



**LEGEND**

1. Access floor panel
2. Roll formed galvanized steel stringer
3. 1/4" - 20 X 1 3/4" screw
4. 8 ga. die formed galv. steel head
5. Steel stud  
7/8" - 9 UNC
6. Locking nut
7. 1" thick fillet welded insert with 7/8" - 9 threaded hole
8. 1-1/4" Schedule 40 steel pipe
9. 6" X 6" X 1/4" steel base plate
10. Fillet weld

## PEDESTAL SPECIFICATIONS

### Pedestal Assembly

- Assembly up to 72" FFH shall provide an 5,000 lb. axial load without permanent deformation.
- Assembly shall provide a 2" total adjustment.
- All pedestal components and fasteners are completely electro-zinc free.

### Pedestal Head

- Standard head is 11 ga. die formed hot dipped galvanized pedestal head with resistance welded stud and adjustment nut.
- Stringers shall be attached with 1/4" - 20 flat-head screws.
- Pedestal head shall be tapped for engagement of stringer screws.
- Steel stud shall be 7/8" - 9 UNC.
- 7/8" - 9 UNC adjustable nut with corrosion resistant coating shall provide anti-rotation feature when engaged with base assembly.

### Pedestal Base

- 1-1/4" Schedule 40 steel pipe (with 1.66" O.D.) fillet welded to 6" X 6" X 1/4" steel base plate.
- 1" thick solid steel 1-1/4" round insert fillet welded onto the top of the steel pipe with 7/8"- 9 threaded hole centered in insert.
- Base plate shall have (4) 9/16" diameter holes at 4.875" center to center distance.
- Assembly shall have rust prohibitive electrocoated epoxy finish.

### Stringers

- Heavy duty roll formed steel stringer shall be 1-1/4" deep X 3/4" wide and shall withstand 450 lb. mid-span load.
- Stringer shall have galvanized coating to prevent corrosion.
- Stringer grid pattern shall be 4' by 4' basketweave.

